


# ServMax® A-28-IN

2U 4Node High Density Server Supporting up to 8x AMD EPYC™ 7003 Series Processors and 8x 2.5” Hot-Swappable U.2 SSD Bays



## Features

- Immersion Cooling Ready – Full warranty provided including both system and components.
- Each node supports two 3rd Gen AMD EPYC™ 7003 series processors with 16x DIMMS.
- Each node has 2x 2.5” Gen4 U.2 hot-swappable SSD bays and 1x M.2 with PCIe Gen4 x4 interface.

### ServMax® A-28-IN System Specifications

Processor Support	• Supports up to 2x 3rd Gen AMD EPYC™ 7003 processors Family per node, max 280W(cTDP)
Memory	• 16x DDR4 RDIMM/LRDIMM per node
Expansion Slots	• 2x Low profile half-length slots with PCIe x16 • 1 x OCP 3.0 mezzanine slot with PCIe Gen4 x16 bandwidth
Storage Front	• Total 4 x Gen4 M.2 M-Key Supports NGFF-2280/22110 cards • Option 1: 8x 2.5 hot-swappable SAS/SATA drives • Option 2: 4x 2.5” hot-swappable SAS/SATA and 4x Gen4 U.2
Rear (Optional)	N/A
Rear Panel	• 2 x USB 3.2 Gen1 • 1 x Mini-DP • 2 x RJ45 • 1 x RJ45 MLAN • 1 x ID LED
Front Panel	• 1 x Power button with LED • 1 x ID button with LED • 1 x Status LED • 1 x System reset button
Management	• 1x ASPEED AST2500 BMC per node, IPMI2.0
Backplane I/O	• 8 x ports support SATA 6Gb/s or SAS 12Gb/s or PCIe Gen4 x4 per port
TPM	• 1x TPM 2.0 Module
Chassis Dimension	3.44” (H) x 17.32” (W) x 24.21” (D) / 87.5mm (H) x 440mm (W) x 840mm(D)

