

AceleMax® AXG-224IB

2U Dual Socket Intel Xeon 6 Processors 6700/6500 Series 4x Dual Slot PCle Al GPU Server



Features

- Supports up to 4 x dual-slot PCIe GPU (H200 NVL, L40S GPU) can be installed in this server
- 2-Socket Intel® Xeon® 6 Processors 6700/6500 series solution
- 3 x PCIe Gen5 x16 Slots for NIC
- 8 x E1.S NVMe SSD bays

Applications

- · Generative AI
- LLM
- Al training
- Inference
- · Industrial digitalization
- · Cloud Computing
- · Virtualized & VDI Applications
- Enterprise & HPC Applications

Specifications	
CPU	Intel Birch-Stream-SP (2-Socket) for GNR (Granite Rapids) support • TDP (Thermal Design Power) is up to 350W with 2U" standard heatsink (Support at Ambient Temperature: 35°C)
GPU Support	4 x Double GPU cards, including NVIDIA L40S or H200 NVL
System Memory	32 x DDR5 DIMM slots; 2DPC (2 DIMM per Channel) • DDR5 RDIMM: 5200MT/s as 2DPC; 6400MT/s as 1DPC
Storage	 8 x PCle Gen5 x4 E1.S NVMe SSD bays (Rear right-hand side) 2 x PCle Gen5 x4 M.2 22110 / 2280 slots for OS usage (Rear middle side)
Expansion Slots	 4 x PCle Gen5 x16 (Front left & right side with MGX 2U Type B Bay) for L40S / H200 NVL 3 x PCle Gen5 x16 (Front middle side) for 2pcs NV Connectx-7 NIC and 1pcs BlueField-3
Front BMC IO	 Power Button / UID button with LED / Status LED 1 x IPMI RJ-45, No On-board LAN to support share-LAN 2 x USB 3.0 port (Compatible USB 2.0) 1 x mini-DP 1 x Micro-USB (For UART Debug) Power Button with LED / UID button with LED
Management and Security	Implement in BMC IO board • (Aspeed / AST2600)
Power Supply	• 1 + 1 3200W Titanium CRPS (Common Redundant Power Supply) with PMBus 1.2 support (Rear Left side)
Dimension	 2U 19" NVIDIA MGX chassis W 438 x H 88 x D 900 mm / W 17.24" x H 3.46" x D 35.43"

